

DWG NO  
1741AS829

SH  
6

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	3075AS260 W/ 3099AS131,	12/2/11	[Signature]
B	REDRAWN, 11 SHEETS WAS 15; REVISED PARAGRAPH D.1.	7/14/10	[Signature]

b) CAB SUPPORT BRACKET ACCESS PLATFORM. (4" WIDE SPACED @ 8" INTERVALS).

c) LADDER RUNGS. (2" WIDE, CONFORMABLE TYPE).

(A) d) MAINTENANCE ACCESS AREAS AS INDICATED ON DRAWING 1764AS205, AACC AND 3075AS260 CVCC. (4" WIDE SPACED @ 8" INTERVALS).

D. RETRO-REFLECTIVE MARKINGS

(A)(B) 1. THE EXTREME PERIMETER OF EACH CRANE SHALL BE MARKED WITH REFLECTIVE TAPE PER ASTM D4956, ROLLS, CLASS I, TYPE 1, COLOR YELLOW, WIDTH 2 INCHES, IN ACCORDANCE WITH MIL-M-81807. (SEE DRAWINGS 1764AS205, AACC & 3075AS260, CVCC)

2. MARKING PROCEDURES:

2.1 THE SURFACES TO WHICH THE TAPE WILL BE APPLIED SHALL BE CLEANED OF ALL LOOSE SCALE, DIRT, OIL AND GREASE; ALL DEPOSITS OF CLEANING COMPOUNDS SHALL BE REMOVED. THE SURFACE SHALL BE THOROUGHLY DRIED.

2.2 THE REFLECTIVE TAPE SHALL NOT BE HAPHAZARDLY APPLIED AND SHALL BE FREE FROM RAGGED EDGES, VOIDS, CRACKS, SCALES, AIR BUBBLES, BLISTERS, AND DIRT.

2.3 APPLY IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. INSURE THAT ALL AIR BUBBLES RE REMOVED WHEN TAPE IS APPLIED. DO NOT APPLY AT TEMPERATURES BELOW 50 DEG. F.

2.4 SEALING COMPOUND (3M PART #735) SHALL BE APPLIED TO THE EDGES OF THE TAPE TO PROTECT THE EDGES FROM FRAYING.

CONTRACT NO:  
N00019-86-C-0028

 LAKE SHORE INC.  
AN OLDENBURG GROUP COMPANY  
IRON MOUNTAIN, MI. 49801  
DWG. NO. 2A1-03004

SIZE A	CAGE CODE 30003	DWG NO 1741AS829	REV B
SCALE NONE	WT -	LBS -	SHEET 6 OF 11